


Panelmonterade intag

Art.nr 1253




- skruvplintar med skyddslock

Tekniska data

Ampere	16 A
Poler	5 p
Volt	400 V
Klockposition	6 h
Hertz	50-60 Hz
Anslutningsteknologi	skruvkontakt
Kontakt	standard
Skyddstyp	IP67
Vikt	302 g
Intyg om överensstämmelse	VDE, EAC

Mått



Drawing	Amp.	16			32			63		
		Poles		3	4	5	3	4	5	
2 MB 62										
Dim. in mm		a	b	c	d	e	f	g	g.1	
		85	85	85	85	85	108	108	108	
		85	85	85	85	85	101	101	101	
		132	132	131	131	137	164	164	164	
		70	70	70	70	70	85	85	85	
		70	70	70	70	70	77	77	77	
		6.3	6.3	6.3	6.3	6.3	6.5	6.5	6.5	
		11	11	11	11	11	12	12	12	
		2	2	2	2	2	2	2	2	
		100	107	108	108	111	130	130	130	
		70	87	94	94	102	114	114	114	
		30	30	30	30	30	40	40	40	
Terminal for cond. cross section (mm ²) min.-max.		1	1	2,5	2,5	2,5	6	6	6	
		-2,5	-2,5	-6	-6	-6	-16	-16	-16	