

Väggmonterat intag

Art.nr 368



- skruvplintar

Tekniska data

| | |
|---------------------------|--------------|
| Ampere | 125 A |
| Poler | 5 p |
| Volt | 400 V |
| Klockposition | 6 h |
| Hertz | 50-60 Hz |
| Anslutningsteknologi | skruvkontakt |
| Kontakt | standard |
| Skyddstyp | IP67 |
| Vikt | 2179 g |
| Intyg om överensstämmelse | EAC, CQC |

Mått



| Drawing | Amp. | 63 | | | 125 | |
|---|------|-------|-------|-------|-----|-----|
| | | Poles | | | 4 | 5 |
| 2 MB 36 | | | | | | |
| Dim. in mm | | | | | | |
| a | | 170 | 170 | 170 | 264 | 264 |
| b | | 118 | 118 | 118 | 163 | 163 |
| c | | 171 | 171 | 171 | 205 | 205 |
| d | | 134.5 | 134.5 | 134.5 | 240 | 240 |
| e | | 103 | 103 | 103 | 140 | 140 |
| f | | 6,1 | 6,1 | 6,1 | 8,1 | 8,1 |
| g | | 6 | 6 | 6 | 8 | 8 |
| h | | 250 | 250 | 250 | 355 | 355 |
| M | | 40 | 40 | 40 | 50 | 50 |
| M* | | 2x40 | 2x40 | 2x40 | 50 | 50 |
| a | | 25° | 25° | 25° | 20° | 20° |
| Max. cable diam. (mm) | | 27 | 27 | 27 | 38 | 38 |
| Terminal for cond. cross section (mm ²) min.-max. | | 6 | 6 | 6 | 16 | 16 |
| | | -16 | -16 | -16 | -35 | -35 |