

## AMAXX receptacle combination

Art.nr 920013




- pre-wired for installation
- hinged to the side
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover

### Tekniska data

CEE 32 A, 5 p, 400 V	1
SCHUKO®	2
Fusing	<ul style="list-style-type: none"> <li>• 1 RCD 40 A, 4 p, 0.03 A</li> <li>• 2 MCB's 16 A, 1 p, C</li> </ul>
Försäkring max.	32 A
InA	32 A
RDF	1
Connection / feeder cable	<ul style="list-style-type: none"> <li>• for 1 cable up to 5 x 10 mm<sup>2</sup></li> </ul>
Skyddstyp	IP44
Slutare	false
Kapslingsmaterial	plast
Vikt	3360 g
Höjd	260 mm
Bredd	225 mm

### Mått



Drawing 1 MB 521

Depth dimensions at various fittings.

Receptacles	Degrees	Depth
SCHUKO® 16A, 230 V	IP 44	175 mm
	IP 67	194 mm
CEE 16A, 3p, 230V	IP 44	204 mm
	IP 67	205 mm
CEE 16A, 5p, 400V	IP 44	209 mm
	IP 67	213 mm
CEE 32A, 5p, 400V	IP 44	221 mm
	IP 67	227 mm
CEE 63A, 5p, 400V	IP 44	248 mm
	IP 67	248 mm

Cable entries: closed for cut out. 2 x M 32 each on top and bottom, 2 x M 20 each on top and bottom for cut out.